

A subsidiary of Green Plains Renewable Energy, Inc.

Emergency Dryer Shutdown

- 1. Turn off
 - a. Air Heater HTRG-11
 - i. This will automatically turn off
 - 1. Paddle mixer X-5208
 - 2. Conveyor X-5209
 - 3. Conveyor X-5230
 - 4. Recycle conveyor X-5206
- 2. Confirm wetcake is now being diverted to the Wetcake Pad.

3. If a Dryer Fire is suspected (things to look for)

- a. Blue steam or smoke coming from dryer stack.
- b. Black steam or smoke coming from RTO stack.
- c. Rising Outlet temp.
- d. Burnt Smell in the air steam.
- 4. If one or all are present Continue with the Shutdown quickly.
- 5. Turn Off
 - a. FN-5202 Recirculation Fan
 - b. FN-5201 Combustion Fan
 - c. FN-5203 Exhaust Fan
- 6. Close
 - a. YV-52199 Fluid Bed Exhaust Damper
 - b. YV-52201 Combustion Air Inlet Damper
 - c. PIC-52111 Hot Air Duct to Dryer
 - d. IIC-5202 Recirc Fan Damper
- 7. Open
 - a. YV-52106 Steam to the Cyclones
 - b. YV-52137 Quench Water to Air Heater
 - c. YV-52136 Quench Water to Air Heater
 - d. YV-52135 Quench Water to Air Heater
 - e. Deluge Water Valves to Cyclones located just inside East door label "Deluge Water to Cyclones"